

### 3 FORMAT STRUCTURE

[...]

#### 3.10 Control Subfields

The group of subfields, defined similarly in many fields throughout the format, used to provide specific identifiers, relationships, sources of terms and codes and to qualify the form recorded in the field. Among their uses are also to provide links to both authority and bibliographic records, to specific institutions, and to other fields within a single record.

The name, description, repeatability and input standard may vary from the field to field.

Valid only for fields where the following subfields are defined:

Subfield	Used in Fields
\$0 Bibliographic Record Identifier	4-- block
\$1 Linking Data	4--block (Embedded Fields Technique), 576 (Embedded Fields Technique), 577 (Embedded Fields Technique), 604 (Embedded Fields Technique)
\$2 Source*	0-- block, 1-- block, 2-- block, 5-- block, 6-- block, 801, 852, 886
\$3 Authority Record Identifier	4-- block, 500, 501, 506, 507, 576, 577, 6-- block, 7-- block
\$4 Relator Code	7-- block
\$5 Institution to which the Field Applies	012, 141, 2-- block, 3-- block, 5-- block, 608, 621, 7--block
\$6 Interfield Linking Data	Where applicable
\$7 Alphabet/Script of Field	Where applicable
\$8 Materials Specified	Where applicable

\*Subfields \$2 in the fields not included in the table are not control subfields.

[...]